

Declaration of Performance

N° 002 RAE 2022 09 29

Extrusions Benelux
Declaration of Performance
0036-CPR-M-078-2014

Hydro Extrusion Raeren S.A.

1. Unique identification code of the product–type:
EN AW-6060 T66
2. Type number allowing identification of the construction product
Extruded rod / bar, tube and profiles according EN 15088
3. Intended uses:
Internal and external structural construction works
4. Name, registered trade name or registered trade mark and contact address
Hydro Extrusion Raeren SA
Waldstrasse, 91
B-4730 RAEREN
Tel : 0032 87 859 211
Fax : 0032 87 859 330
Internet: www.hydro.com/raeren
5. Name and contact address of the authorized representative
Not applicable
6. System or systems of assessment and verification of constancy of performance of the construction product
System 2+
7. Case of the declaration of performance concerning a construction product by a harmonized standard
TÜV Süd Industrie Service GmbH, No. 0036, has performed the initial inspection of factory and factory production control and monitoring, review and approval of the factory production control according to system 2+ and issued conformity certificates of production control for the plant
Hydro Extrusion Raeren 0036-CPR-M-078-2014
8. Case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:
Not applicable

9. Declared performance

Essential Characteristic	Performance										Harmonised technical specification		
Tolerance on dimensions and shape	Tolerances on dimensions										EN 15088 : 2005		
	Cross –sectional dimensions												
	Length												
	Squareness of cut ends												
	Tolerances on form												
	Straightness												
	Convexity-Concavity												
	Contour												
	Twist												
	Angularity												
Corner and fillet radii													
Tensile strength	Extruded rod / bar Dimensions (mm)										EN 15088 : 2005		
	EN 755-2:2016												
	T66												
	D ^a					S ^b						R _m (MPa)	
	≤ 150					≤ 150						215	
	Extruded tube Wall Thickness t (mm)												
	≤ 15												
	Extruded profile Wall thickness t (mm)												
≤ 3													
3 < t ≤ 25													
Yield strength	Extruded rod / bar Dimensions (mm)										EN 15088 : 2005		
	EN 755-2:2016												
	D ^a					S ^b						R _{p0.2} (Mpa)	
	≤ 150					≤ 150						160	
	Extruded tube Wall Thickness t (mm)												
	≤ 15												
	Extruded profile Wall thickness t (mm)												
	≤ 3												
3 < t ≤ 25													
Elongation	Extruded rod / bar Dimensions (mm)										EN 15088 : 2005		
	D ^a					S ^b						A (%)	
	≤ 150					≤ 150						8	
	Extruded tube Wall Thickness t (mm)												
	≤ 15												
	Extruded profile Wall thickness t (mm)												
	≤ 3												
	3 < t ≤ 25												
8													
6													
Weldability	No performance determined												
Bendability	No performance determined												
Fatigue strength	No performance determined												
Regulated substance	No performance determined												
Durability	No performance determined												
Chemical composition	Si	Fe	Cu	Mn	Mg	Cr	Zn	Ti	remarks	others	aluminium	EN 15088 : 2005	
	0,30	0,10			0,35						Remainder		
	0,6	0,30	0,10	0,10	0,6	0,05	0,15	0,10		0,05	0,15		

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of Hydro Extrusion Raeren S.A. by

Marcel ANDRATSCHKE Quality Manager

Raeren

29/09/2022