

<b>Declaration of Performance (DoP)</b>										
<b>In compliance with EU regulation 305/2011, Annex III</b>										
For the construction product					<b>Extruded aluminium sections</b>					
1. Unique identification code of the product type :					<b>EN AW-6063 T66 / EN 755-9</b>					
2. Type, batch or serial number or any other element allowing identification of the construction product in compliance with Article 11(4):					Extruded section according to 15008:2005 / EN AW-6063 T66 according to EN 755-1					
3. Use(s) of the construction product intended by the manufacturer in compliance with the applicable harmonized technical specification:					Indoor and outdoor areas of load-bearing structures					
4. Name, registered trade name or registered trade mark and contact address of the manufacturer in compliance with Article 11(5):					<b>Hydro Extrusion Albi SAS</b> ZA Jean Savy – France 81450 Le Garric Tel : +33 (0) 563801010 ; fax : +33 (0) 563547756 E-mail : info.profilesalbi.fr@sapagroup.com					
5. Name and contact address of the authorized representative commissioned with the tasks under Article 12 (2), if any:					<b>Not appointed</b>					
6. System(s) for assessment and verification of constancy of performance of the construction product in compliance with Annex V:					<b>System 2+</b>					
7. If the declaration of performance concerns a construction product that is covered by a harmonized standard:					The notified body ( <b>Karlsruhe Institute of Technology no. 0769</b> ) performed the initial inspection of the manufacturing plant and of factory production control, as well as continuous surveillance, assessment and evaluation of factory production control in compliance with System 2+ and issue certificate <b>0769-CPR</b> confirming conformity of the factory production control with the requirements set out in Annex ZA of EN 15088:2005					
8. If the declaration of performance concerns a construction product for which a European Technical Assessment was issued:					<b>Not applicable</b>					
9. Performance declared:										
<b>Essential characteristics</b>			<b>Performance</b>					<b>Harmonized technical specification</b>		
<b>Dimensional and shape tolerances</b>			In compliance with standard					EN 755-9		
<b>Mechanical characteristics</b>			In compliance with standard							
<b>Profiles</b>			<b>Tensile strength R<sub>m</sub> [MPa]</b>		<b>Yield strength R<sub>p0.2</sub> [MPa]</b>		<b>Elongation A [%]</b>	<b>Elongation A<sub>50mm</sub> [%]</b>	<b>HBW typical value</b>	
<b>Wall thickness t (mm)</b>			min.	max.	min.	max.	min.	min.		
≤ 10			245	NPD	200	NPD	8	6	80	
10 < t ≤ 25			225	NPD	180	NPD	8	6	80	
<b>Weldability</b>			Class I					EN 1999-1		
<b>Bendability</b>			B3							
<b>Fatigue strength</b>			NPD					EN 1999-1-3		
<b>Wear resistance</b>			Table 3.1a					EN 1999-1		
<b>Chemical composition</b>		<b>Elements</b>	<b>Si</b>	<b>Fe</b>	<b>Cu</b>	<b>Mn</b>	<b>Mg</b>	<b>Cr</b>	<b>Ni</b>	<b>Zn</b>
		min	0.20	-	-	-	0.45	-	-	-
		max	0.60	0.35	0.10	0.10	0.90	0.10	-	0.10
		<b>Elements</b>	<b>Ti</b>	<b>Ga</b>	<b>V</b>	<b>Other (each)</b>	<b>Other (total)</b>	<b>Al</b>	<b>Remark</b>	
		min	-	-	-	-	-	Rest		
		max	0.10	-	-	0.05	0.15			
10. The performance of the product according to numbers 1 and 2 is in accordance with the performance declared according to number 9. Only the manufacturer under 4 is responsible for preparing this declaration of performance.										

Signed for and on behalf of the manufacturer by:

Name and function:



Frédéric Hestroffer (Quality manager)

Place, date, signature:

Le Garric, le 05/09/2018